



CHART A

| Torch Model          | Amps | Nozzle                      | Length (A) |
|----------------------|------|-----------------------------|------------|
| WT-22A,B<br>WT-23A,B | 260  | Standard Nozzle             | 1 5/16"    |
|                      |      | Long Nozzle<br>1 7/8"       | 2 1/16"    |
|                      |      | Extra Long Nozzle<br>2 1/2" | 2 13/16"   |
|                      | 130  | Gas Lens Nozzle             | 1 3/16"    |
|                      |      | Medium Dia. Gas Lens Nozzle | 1 7/16"    |
|                      |      | Large Dia. Gas Lens Nozzle  | 2 1/16"    |
| WT-28A,B<br>WT-29A,B | 350  | Standard Nozzle             | 2 3/16"    |
|                      |      | Long Nozzle<br>3"           | 3 5/16"    |
|                      | 180  | Gas Lens Nozzle             | 2 1/4"     |
|                      |      | Large Dia. Gas Lens Nozzle  | 2 3/8"     |

### SPECIFICATIONS

| Torch Model      | Maximum Amps (ac-dcsp) | Duty Cycle (ac-dcsp) | Tungsten Capacity | Max. Length | Cooling Requirements                               |
|------------------|------------------------|----------------------|-------------------|-------------|--|
| WT-22A<br>WT-22B | 260                    | 60%                  | .020 - 1/8        | 7"<br>14"   | Water Cooled<br>1 Qt./min.<br>(50 psi MAX. OUTPUT) |
| WT-23A<br>WT-23B | 130                    | 60%                  | .020 - 3/32       | 7"<br>14"   | Air Cooled   |
| WT-28A<br>WT-28B | 350                    | 60%                  | .020 - 5/32       | 7"<br>14"   | Water Cooled<br>1 Qt./min.<br>(50 psi MAX. OUTPUT) |
| WT-29A<br>WT-29B | 180                    | 60%                  | .020 - 1/8        | 7"<br>14"   | Air Cooled   |

COPYRIGHT 2000 - 2019 TEC WELDING PRODUCTS, INC.

Note: Specifications and dimensions are subject to change without notice.